Event Detection in Videos Using a Graph Convolutional Network

Daiki Mukai¹, Kimiaki Shirahama¹, Takashi Matsubara² and Kuniaki Uehara³ 1. Kindai University, 2. Osaka University, 3. Osaka Gakuin University

Motivation

An event is characterized by specific object appearances and their spatial-temporal relations



Need for capturing spatial-temporal relations among objects involved in an event

Use Spatial-Temporal Graph Convolutional Network (ST-GCN)


The visual feature of an object is abstracted into a high-level one by integrating features of spatially and temporally close objects.

Graph Creation

Segment of 20 frames sampled every 5 frames



- M2Det for object detection
- SE-ResNeXT-101 for feature extraction



- Spatial connections: Objects in the same frame are connected if they are close to each other
- Temporal connections: Two objects in consecutive frames are connected if their features are very similar

ST-GCN for Event Detection

Convolution needs the order of the data



$$w=(w_1,w_2,\cdots,w_9)^T$$


No order of nodes in a graph Define the partitions for a node v_i

- $B_1 = \{v_i\}$
- $B_2 = \{v_i \mid d(v_i, v_j) = 1\}$

$$f_{out}(v_i) = f_{in}(v_i)w(p(v_i))$$


$$+ \sum_{v_i \in B_2(v_i)} \frac{1}{|p(v_j)|} f_{in}(v_j)w(p(v_j))$$

Abstract v_i 's feature using a filter for itself and the another filter for neighboring nodes



Sigmoid 36 classes

Result Overview




- 5,247 segments for training
- 21,489 segments for testing
 The partial AUDC of our method is 0.9682

The main reason is to only output the event occurrence with the highest probability for a segment.

Optimize filters so as to achieve accurate event detection

Discussion



←

Result of detecting multiple event occurrences for one segment

Many objects in a frame

Global average pooling mixes features of relevant and irrelevant objects to an event



Adopt an attention mechanism to selectively weight each object's features

